

PRODUCT DATA SHEET

PaperWise White - BioTAK® XS102

PWW75.XS102



FACESTOCK

DESCRIPTION	A white high-quality paper-like material made from agricultural waste (leaves and stems); uncoated
THICKNESS	104 µm
YIELD	75 g/m2

ADHESIVE - BIOTAK®



DESCRIPTION	BioTAK® is a permanent acrylic adhesive
TACK	12.5N/25mm FTM 9 Glass
PEEL ADHESION 90°	7N/25mm FTM 2 St.St.
MIN. APPL. TEMP.	5°C
SERVICE TEMP.	-20°C to 80°C

LINER

DESCRIPTION	The liner is a white glassine paper
THICKNESS	55 µm
YIELD	62 g/m2

ABOUT

TOTAL CALIPER	169 µm ± 10%
PRINTING	The matt white material is ideal for sharp printing in both black and full colour. Printable by conventional as well as digital printing techniques.
APPROVALS	Adhesive is certified compostable, compliant to EN13432 For direct food application in compliance with EC1935/2004 & FDA 175.105
STORAGE CONDITIONS	Storage at a temperature of 20 ± 5°C, a relative humidity of 45 ± 5 % is recommended. Moisture, heat and direct sunlight must be avoided.
SHELF LIFE	The shelf life is up to 1 year from date of production.
APPLICATIONS	The material is a sustainable alternative to conventional white paper labels. For all applications we recommend testing the performance of the material.

Disclaimer: All technical information and recommendations are based on our knowledge and experience of the product but do not constitute a warranty or guarantee. Although we make every effort to ensure that all information is correct, we accept no liability for any errors or omissions. The content of this document is given for information purposes only and does not provide any guarantee or warranty that the product is suitable for the client's specific use.

Version 07.22